

## DESCRIPTION

The HS-150B is a 2-way speaker system made of resin, and features a large diameter woofer. It can be installed and used in many different applications with combined use of the supplied accessories and/or the optional mounting brackets.

## SPECIFICATIONS

|                         |   |
|-------------------------|---|
| Enclosure               | Sealed type   |
| Power Handling Capacity | Continuous pink noise: 100 W, Continuous program: 300 W   |
| Rated Impedance         | 8 Ω   |
| Sensitivity             | 98 dB (1 W, 1 m)  |
| Frequency Response      | 70 Hz - 20 kHz  |
| Crossover Frequency     | 3 kHz   |
| Directivity Angle       | Horizontal: 90°, Vertical: 40°  |
| Speaker Component       | Low frequency: 38 cm (15") cone-type, High frequency: Balanced dome tweeter × 6   |
| Input Terminal          | NEUTRIK NL4MPXX Speakon and M4 screw terminal, distance between barriers: 9 mm (0.35")  |
| Operating Temperature   | -10 °C to +50 °C (14 °F to 122 °F)  |
| Finish                  | Enclosure: Polypropylene, black<br>Punched net: Surface-treated steel plate, black  |
| Dimensions              | 451 (W) × 560 (H) × 400 (D) mm (17.76" × 22.05" × 15.75")   |
| Weight                  | 12 kg (26.46 lb)  |
| Accessory               | Handle ×1, Handle fitting bracket ×2, Handle mounting screw ×2, Rubber foot ×2, Rubber foot mounting screw ×2   |
| Option                  | Mounting bracket: HY-1500VB (for vertical speaker mounting)<br>HY-1500HB (for horizontal speaker mounting)<br>Ceiling mount bracket: HY-C0801<br>Wall mounting bracket: HY-W0801<br>Speaker stand: ST-34B |

## APPEARANCE

