

## DESCRIPTION

The HS-150B is a 2-way speaker system made of resin, and features a large diameter woofer. It can be installed and used in many different applications with combined use of the supplied accessories and/or the optional mounting brackets.

## SPECIFICATIONS

Enclosure	Sealed type
Power Handling Capacity	Continuous pink noise: 100 W, Continuous program: 300 W
Rated Impedance	8 Ω
Sensitivity	98 dB (1 W, 1 m)
Frequency Response	70 Hz - 20 kHz
Crossover Frequency	3 kHz
Directivity Angle	Horizontal: 90°, Vertical: 40°
Speaker Component	Low frequency: 38 cm (15") cone-type, High frequency: Balanced dome tweeter × 6
Input Terminal	NEUTRIK NL4MPXX Speakon and M4 screw terminal, distance between barriers: 9 mm (0.35")
Operating Temperature	-10 °C to +50 °C (14 °F to 122 °F)
Finish	Enclosure: Polypropylene, black Punched net: Surface-treated steel plate, black
Dimensions	451 (W) × 560 (H) × 400 (D) mm (17.76" × 22.05" × 15.75")
Weight	12 kg (26.46 lb)
Accessory	Handle ×1, Handle fitting bracket ×2, Handle mounting screw ×2, Rubber foot ×2, Rubber foot mounting screw ×2
Option	Mounting bracket: HY-1500VB (for vertical speaker mounting) HY-1500HB (for horizontal speaker mounting) Ceiling mount bracket: HY-C0801 Wall mounting bracket: HY-W0801 Speaker stand: ST-34B

## APPEARANCE

